


COB LED Strip Specification

CZ-220-08-288-10-XX





CZ-220-08-288-10-XX



Description



This product is a high-density COB-288 Lamp, 220V, 8mm Width, 4000K, CRI Ra70, Milky White Potting Encapsulation. It adopts an on-board integrated packaging process, ensuring uniform light distribution without dark areas and providing soft illumination. With low-voltage power supply for safe and reliable operation, the flexible substrate allows bending and cutting, offering strong adaptability in design. It is widely used in residential, commercial, and outdoor landscape lighting applications.



RoHS



Dimensions & Waterproof



Product Specification

Dimension	5000*8*6.0 MM
Chip Type	Sanan
Chips/m	288
lumens	650-750 Lm
Step Length	500MM
Color Rendering Index	≥70


Voltage(V)	220V
Power(W/m)	10 W/M
PCB Width	8 MM
Beam Angle	160°
Operation Temperature	-20°C~+ 45°C
Color Temperature	2700K/3000K/4000K/6000K

Product Photometrics (Data base on IP65 CRI≥70)

Part Number	CCT (K)	Power(10w/m)	
		Lumen (lm/m)	Efficacy (lm/w)
▶288D-COBW27-220V-8MM	2700K ±150K	550-600	55-60
▶288D-COBW30-220V-8MM	3000K ±150K	550-650	55-65
▶288D-COBW40-220V-8MM	4000K ±200K	650-750	65-75
▶288D-COBW60-220V-8MM	6000K ±250K	550-650	55-65




Light Distribution Curve[Data base on 1m 10W IP65 4000K CRI>70, Unit:cd]




Color Parameters:

Chromaticity Coordinate: $x=0.4013$ $y=0.4010$ $u'=0.2290$ $v'=0.5149$
 CCT=3670K (Duv=0.0054) Dominant WL:Ld =578.1nm WL:Lc = --nm Purity=40.8%
 Ratio:R=18.25% G=79.89% B=1.86% Peak WL:Lp=583.9nm FWHM=143.9nm


Packing Information(Data base on IP65)




5meters/reel



5meters/reel



100bags/carton



43.5x32x23.5cm,8.5kg/carton

Precautions for use

1. To protect the LED light strip, do not hit the light-emitting area with hard things.
2. After unpacking, please use in 24H to avoid the oxidation effect of solder joints.
3. Avoid direct contact with high temperature objects in the light-emitting area of the lamp, and the instantaneous contact temperature of the surface of the light-emitting area should be less than 210 °C.
4. The soldering iron temperature should be less than 300 during soldering, and the soldering time of single solder should be controlled within 3s.
5. It is strictly forbidden to twist the lamp with short distance. The single lamp strip (0.5 m) has a maximum twist angle of 720°.
6. The bend diameter at any position needs to be greater than 1cm.